

Product Selection Guide

	POWDER COATED STEEL	STAINLESS STEEL	SOLID PLASTIC	PLASTIC LAMINATE	PHENOLIC ⁽¹⁾
APPLICATION	Durable quality at affordable price. Most frequently specified. Wide color selection.	Strength combined with sophisticated resilience. Proven performance in busy applications.	Ideal for humid conditions and high traffic facilities. Graffiti and impact resistant.	Design flexibility with numerous colors at economic cost for dry environments. Will not rust.	Color versatility. Resists water, oil bacteria and marring. Will not dent or delaminate.
RELATIVE COST (Powder =100%)	100%	265%	190%	110%	240%
WARRANTY	3 Years	5 Years	15 Years	2 Years	10 Years
COLOR OPTIONS	18 Standard Colors	Type 304 with #4 brush finish (Textured patterns also available)	14 Standard Colors	36 Standard Colors	10 Standard Colors & 5 Color-Thru
VANDAL RESISTANCE	★ ★	★ ★ ★ ★ ★	★ ★ ★ ★	★ ★	★ ★ ★ ★ ⁽²⁾
MOUNTING STYLES					
Floor Anchored/Overhead Braced	●	●	●	●	●
Floor Mounted	●	●		●	●
Ceiling Hung	●	●	●	●	●
Floor-to-Ceiling	●	●	●	●	●
HARDWARE					
<i>STIRRUP BRACKETS</i>					
Chrome Plated Zamac	●	●		●	
Stainless Steel	●	●		●	●
Aluminum					
<i>CONTINUOUS BRACKETS</i>					
Stainless Steel	●	●	●	●	●
Aluminum	●	●	●	●	
Plastic			●		
<i>HINGES</i>					
Zamac	●	●		●	
Stainless Steel	●	●		●	
Integral			●		
Vault			●		●
Full height piano hinge	●	●	●	●	●
CONSTRUCTION					
Door Thickness	1"	1"	1"	1"	3/4"
Panel Thickness	1"	1"	1"	1"	1/2"
Pilaster Thickness	1 1/4"	1 1/4"	1"	1 1/4"	3/4"
Urinal Screen Thickness	1"	1"	1"	1"	1/2"

(1) Class "A" fire rated available (2) Color-Thru