

Solid Plastic Vanities

4.17

Solid Plastic Vanities

Part 1 - General

1.01 Work Included

A. The restroom vanities shall be high-density polyethylene (HDPE) polymer as manufactured by **Accurate Partitions Corp.**, Lyons, Illinois.

B. Furnish all labor and materials necessary for completion of work in this section as shown in the approved drawings and specified herein.

1.02 Related Work – Specified elsewhere shall include accessories and anchorage/blocking for attachment of vanities.

Part 2 – Product

2.01 Vanity, Back splash, Side splash, Apron and Support – Shall be 1” thick, HDPE that is water-resistant and non-absorbent.

2.02 Material – The HDPE material shall have homogeneous color throughout with ¼” machined edges.

2.03 Construction – Vanity top shall be standard width of 24” with a maximum length of 120” for single piece. Apron, back splash, and side splash shall be a standard height of 4” and have a maximum length of 120”.

2.04 Hardware – HDPE vanity supports shall be secured to the vanity top and the base shall have a PVC trim shoe. The vanity top shall also be secured to the wall by anodized aluminum brackets.

Part 3 – Execution

3.01 Installation – Shall be installed in accordance to the **Accurate** installation instructions with compartments rigid, straight and plumb.

3.02-Warranty – Accurate Partitions Corp. Guarantees its solid plastic HDPE material against breakage, corrosion and delamination for 15 YEARS from the date of receipt by the customer. If material is found defective during that period, the materials shall be replaced free of charge. No credits or allowances shall be issued for any labor or expenses relating to the replacement of components covered under the warranty plan.