

Phenolic Partitions Ceiling Hung 6.9

Phenolic Partitions with Ceiling Hung Mounting Style

Part 1 - General

1.01 Work Included

A. The toilet partitions shall be phenolic material with ceiling hung mounting style as manufactured by **Accurate Partitions Corp.**, Lyons, Illinois.

B. Furnish all labor and materials necessary for completion of work in this section as shown in the approved drawings and specified herein.

1.02 Related Work – Specified elsewhere shall include accessories and anchorage/blocking for attachment of partitions.

Part 2 – Product

2.01 Doors and Pilasters – Shall be $\frac{3}{4}$ " thick solid phenolic core and decorative surface sheet on both faces.

2.02 Panels and Urinal Screens – Shall be $\frac{1}{2}$ " thick solid phenolic core and decorative surface sheet on both faces.

2.03 Material – Doors, panels, pilasters and urinal screens shall be fabricated from phenolic material comprised of multiple layers of melamine resin impregnated kraft paper, and a decorative surface sheet on both faces. All layers shall be fused together under high temperature and pressure.

2.04 Finish – All components shall be water-resistant. Rough edges shall be machine sanded with a 45 degree radius edge and black finish.

2.05 Color - Shall be selected from **Accurate's** full range of standard designer colors.

2.06 Door Hardware – Shall be **Accurate** gravity cam-action hinge that permits door to return to a pre-set position when not locked. Hinge, strike and keeper shall be brushed aluminum to resist corrosion and through bolted with tamper resistant barrel nuts and shoulder screws. Cam-action hinge shall allow emergency access by lifting the door from the bottom.

2.07 Mounting Hardware –Stainless steel stirrup brackets with brushed finish shall be secured to walls and pilasters with stainless steel tamper resistant fasteners. Panels shall be through bolted with tamper resistant barrel nuts and shoulder screws.

2.08 Construction Design – Partitions shall be ceiling hung with $\frac{3}{8}$ " x 1" steel mounting bar attached to the top of the pilaster. Each mounting bar shall be secured to the overhead structural member with two $\frac{3}{8}$ " cadmium-plated bolts. The ceiling anchoring system shall be concealed by a type 304 stainless steel trim shoe with a #4 finish.

Part 3 – Execution

3.01 Installation – Shall be installed in accordance to the **Accurate** installation instructions with partitions rigid, straight and plumb. Doors and panels shall be mounted 12" above the finished floor.

3.02 Warranty – **Accurate Partitions Corp.** guarantees its phenolic partitions, properly maintained, against delamination, breakage or corrosion for 10 YEARS from the date of receipt by the customer. If material is found defective during that period, the material shall be replaced free of charge. No credits or allowances shall be issued for any labor or expenses relating to the replacement of components covered under the warranty plan.